

XANADU™ 200 SERIES TECHNICAL SPECIFICATIONS

Model Name			Xanadu 220	Xanadu 230
RAID Levels			0, 1, 1+0, 5, 6	
Number of Controllers			Max. 4	Max. 8
Host Interface			Fibre-Channel (Max. 8Gbps), iSCSI (Max. 1Gbps)	
Number of Host Interfaces	Fibre-Channel		4 - 64	16 - 128
	iSCSI		4 - 32	4 - 64
Cache Capacity			Max. 256GB	Max. 512GB
Number of Disk Drives			Max. 1020	Max. 2760
Disk Drive Type			SATA, FC, SSD	
Drive Interface			Fibre-Channel (4Gbps)	
Dimensions [W x D x H] (w/Expansion Cabinet)			29.13" x 39.17" x 70.87" (151.18" x 39.17" x 70.87")	53.54" x 39.17" x 70.87" (151.18" x 39.17" x 70.87")
			9,325.55 lbs.	24,096.53 lbs
Power Requirements	Voltage		AC200-240V	
	No. of Phases		Single	
	Frequency		50/60Hz	
Max Power Consumption			36,700 W	96,400 W
Max Heat Dissipation			132,200 KJ/h	347,100 KJ/h
Environmental Conditions	Temperature		41 - 95°F (Operating), 32 - 122°F (Non-Operating)	
	Humidity		20 - 80%RH (Operating), 8 - 80%RH (Non-Operating)	
Regulatory	Electromagnetic Emissions and Immunity		FCC Class A, CE Mark, EN55024 Immunity, EN55022 Class A, VCCI Class A (For Japan), AS/NZS 3548 Class A (For Australia / New Zealand)	
	Safety, Quality, and Environmental Standards		UL60950-1, CSA60950-1 EN60950-1, IO9001, ISO14001	
Supported OS			Windows Server 2000 / 2003 / 2008, Red Hat Enterprise Linux 3 / 4 / 5, Solaris 8 / 9 / 10, SUSE Linux Enterprise Server 9 / 10, VMWare ESX Server 2, 3.0, 3.5, HP-UX 11iv2 / 11iv3, AIX 5.2 / 5.3	